

2000 SERIES STANDARD DUTY RIM EXIT DEVICE



AL Painted



Specification

ANSI: Meets ANSI A156.3 - Grade 1 Standards

UL Listings: UL Listed for Panic Exit Hardware
UL Listed for "A" Label 3 Hour Fire Doors

ADA: Meets ADA requirements ANSI A117.1 with Lever Trim

Handing: Non-handed - Completely Reversible

Construction: Roll Formed Steel or Stainless Steel Channel & Steel Chassis
Steel or Stainless Steel Headcover & End Cap

Finishes: Aluminum, Dark Bronze, Gold Painted & US32D

Latchbolt: Deadlocking latchbolt with 5/8" projection

Strike: Roller Strike with 5/8" projection with 1/8" shim

Dogging: 5/32" Hex Key Dogging Standard on Panic Exit Hardware

Device Lengths: 33" for 3'-0" wide doors and 42" for 3'-8" to 4'-0" wide doors

Min. Door Width: 33" device can be cut down to fit on 2'-8" wide door
42" device can be cut down to fit on 3'-4" wide door

Center Case Dim.: 6" Height x 2 5/16" Wide x 2 1/2" Thick - 4" Minimum stile required

Mechanism Case Dim.: 1 5/8" Height x 1 13/16" Wide

Projection: 2 1/2" Undogged - Push bar Neutral & 1 13/16" Dogged - Push bar Depressed

Fasteners: Wood, machine & self tapping machine screws (F2000R includes thru bolts)

Alarmed Exits: Exit Alarm Kit ALK-2000 available for new or existing devices

Trim & Accessories: ASA & latch filler included, Exterior Trims, Shim Kits & other accessories available

Warranty: Limited lifetime warranty



US32D



Gold Painted

BZ Painted